

UNI-T

UTP3705



SPECIFICATIONS

Feature		UTP3705
Output Voltage	Ch1, Ch2	0~32V
	Ch3	
Output Current	Ch1, Ch2	0~5A
	Ch3	
Overload Effect		$CV \leq 1 \times 10^{-4} + 2mV$, $CC \leq 2mA$
Ripple & Noise		$CV \leq 1mV_{rms}$, $CC \leq 1mA_{rms}$
Regulation		CV - 20mV (Typical Value), CC - 50mV (Typical Value)
Tracking Error		$5 \times 10^{-3} + 2mV$
Reliability		MTBF (e): ≥ 2000 hours
Other Features		Triple Output, Series or Parallel Operation, Current Limitation Auto Switching Between Voltage and Current Operation

GENERAL CHARACTERISTICS

Power	220V \pm 10%, 50Hz \pm 4%
Product Color	Red and Grey
Product Net Weight	Around 4kg
Product Size	210mm x 152mm x 305mm
Standard Accessories	Test Lead, English Manual and Power Cord
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	600 x 380 x 245mm (0.056 CBM Per Export Carton)
Standard Carton Gross Weight	9.5kg